

Dimmer T8 Tube Light





CRI >80, CE,ROHS compliant,
PF > 0.95, 100% 4000V high-voltage test, no glare,
no interference, triac dimmable.

Long lifetime, energy-saving,
high bright 3014 LEDs,
single-end isolated driver,
good thermal management, high lumen, l
ight efficiency >110 lm/w, 5 years warranty,
highly cost effective,



Size:(mm)



A: 0.6M=594mm 0.9M=908mm 1.2M=1212mm
1.5M=1512mm 1.8M=1778mm 2.4M=3385mm
B: 0.6M=580mm 0.9M=894mm 1.2M=1198mm
1.5M=1498mm 1.8M=1764mm 2.4M=2371mm
C: 12.7mm 17mm 8mm

Model number	CCT	Light output ($\pm 10\%$ lm)	Length mm	CRI
--------------	-----	----------------------------------	--------------	-----

Clear

AIT8-009-AH-WW-01C	2800-3200K	869	600	≥ 80
AIT8-009-AH-NW-01C	4000-4500K	913	600	≥ 80
AIT8-009-AH-W-01C	5700-6300K	918	600	≥ 80
AIT8-014-AH-WW-01C	2800-3200K	1352	900	≥ 80
AIT8-014-AH-NW-01C	4000-4500K	1419	900	≥ 80
AIT8-014-AH-W-01C	5700-6300K	1382	900	≥ 80
AIT8-018-AH-WW-02C	2800-3200K	1875	1200	≥ 80
AIT8-018-AH-NW-02C	4000-4500K	1973	1200	≥ 80
AIT8-018-AH-W-02C	5700-6300K	1979	1200	≥ 80
AIT8-022-AH-WW-01C	2800-3200K	2193	1500	≥ 80
AIT8-022-AH-NW-01C	4000-4500K	2458	1500	≥ 80
AIT8-022-AH-W-01C	5700-6300K	2517	1500	≥ 80
AIT8-028-AH-WW-01C	2800-3200K	2565	1800	≥ 80
AIT8-028-AH-NW-01C	4000-4500K	2892	1800	≥ 80
AIT8-028-AH-W-01C	5700-6300K	2927	1800	≥ 80
AIT8-036-AH-WW-01C	2800-3200K	3235	2400	≥ 80
AIT8-036-AH-NW-01C	4000-4500K	3450	2400	≥ 80
AIT8-036-AH-W-01C	5700-6300K	3518	2400	≥ 80

Frost

AIT8-009-AH-WW-01F	2800-3200K	738	600	≥ 80
AIT8-009-AH-NW-01F	4000-4500K	780	600	≥ 80
AIT8-009-AH-W-01F	5700-6300K	774	600	≥ 80
AIT8-014-AH-WW-01F	2800-3200K	1189	900	≥ 80
AIT8-014-AH-NW-01F	4000-4500K	1215	900	≥ 80
AIT8-014-AH-W-01F	5700-6300K	1194	900	≥ 80
AIT8-018-AH-WW-02F	2800-3200K	1589	1200	≥ 80
AIT8-018-AH-NW-02F	4000-4500K	1651	1200	≥ 80
AIT8-018-AH-W-02F	5700-6300K	1656	1200	≥ 80
AIT8-022-AH-WW-01F	2800-3200K	1991	1500	≥ 80
AIT8-022-AH-NW-01F	4000-4500K	2047	1500	≥ 80
AIT8-022-AH-W-01F	5700-6300K	2116	1500	≥ 80
AIT8-028-AH-WW-01F	2800-3200K	2223	1800	≥ 80
AIT8-028-AH-NW-01F	4000-4500K	2477	1800	≥ 80
AIT8-028-AH-W-01F	5700-6300K	2536	1800	≥ 80
AIT8-036-AH-WW-01F	2800-3200K	2899	2400	≥ 80
AIT8-036-AH-NW-01F	4000-4500K	3041	2400	≥ 80
AIT8-036-AH-W-01F	5700-6300K	3115	2400	≥ 80

