

Economical 2 x 2 LED Panel Light

PC cover, 120 degree high temperature resistant.
Two options: frosted and wave lens.

white housing, RAL9003.
6063 aluminum frame and
aluminum PCB plate makes
excellent heat dissipation
performance.




LED driver : isolated constant current design,
low heat, and high efficiency up to 85%, PF>0.95.




LED: high efficiency 2835 SMD LED.




Size:(mm)



Model number	CCT	Light output (±10%)lm	CRI
AI-GL-45-AW-01W-6060	5500-6500K	4010	>80
AI-GL-45-AW-01NW-6060	3900-4500K	4480	>80
AI-GL-45-AW-01WW-6060	2700-3200K	3840	>80




AI-GL-45-AW-01W-6060




AI-GL-45-AW-01NW-6060




Size:(mm)



Model number	CCT	Light output (±10%)lm	CRI
AI-GL-60-AW-01W-6060	5500-6500K	5100	>80
AI-GL-60-AW-01NW-6060	3900-4500K	5560	>80
AI-GL-60-AW-01WW-6060	2700-3200K	4520	>80




AI-GL-60-AW-01W-6060




AI-GL-60-AW-01NW-6060




Size:(mm)



Model number	CCT	Light output (±10%)lm	CRI
AI-GL-35-AW-01-CW-C	5500-6500K	3030	>80
AI-GL-35-AW-01-NW-C	3900-4500K	2830	>80
AI-GL-35-AW-01-WW-C	2700-3200K	2650	>80




AI-GL-35-AW-01CW-6060




AI-GL-35-AW-01NW-6060




Size:(mm)



Model number	CCT	Light output (±10%)lm	CRI
AI-GL-45-AW-01-CW-C	5500-6500K	3910	>80
AI-GL-45-AW-01-NW-C	3900-4500K	3900	>80
AI-GL-45-AW-01-WW-C	2700-3200K	3590	>80




AI-GL-45-AW-01CW-6060




AI-GL-45-AW-01NW-6060




Size:(mm)



Model number	CCT	Light output (±10%)lm	CRI
AI-GL-55-AW-01-CW-C	5500-6500K	4920	>80
AI-GL-55-AW-01-NW-C	3900-4500K	4870	>80
AI-GL-55-AW-01-WW-C	2700-3200K	4430	>80



AI-GL-55-AW-01CW-6060



AI-GL-55-AW-01NW-6060

