

## High Brightness T8 Tube Light



CRI >80, UL/TUV/ERP/DLC compliant,  
PF > 0.95,  
100% 4000V high-voltage test, no glare,  
no interference.

SMD 2835 LEDs, single-end isolated driver,  
good thermal management, high lumen,  
light efficiency >100 lm/w.

Oval tube, rotatable end cap available,  
long lifetime, energy-saving, high bright,  
5 years warranty, highly cost effective.




Size:(mm)




A: 0.4m±0.05mm 1.2m±1.213mm 1.5m±1.513mm  
 B: 0.4m±0.08mm 1.2m±1.199mm 1.5m±1.499mm  
 C: 12.7mm


Model number	CCT	Light output (±10%,lm)	LED Q'ty	CRI
<b>Frosted</b>				
AIT8-009-AW-W-01F	5700-6300K	916	52	≥ 80
AIT8-009-AW-NW-01F	4000-4500K	877	52	≥ 80
AIT8-009-AW-WW-01F	2800-3200K	832	52	≥ 80
AIT8-018-AW-W-01F	5700-6300K	1945	110	≥ 80
AIT8-018-AW-NW-01F	4000-4500K	1851	110	≥ 80
AIT8-018-AW-WW-01F	2800-3200K	1745	110	≥ 80
AIT8-022-AW-W-01F	5700-6300K	2433	130	≥ 80
AIT8-022-AW-NW-01F	4000-4500K	2262	130	≥ 80
AIT8-022-AW-WW-01F	2800-3200K	2184	130	≥ 80
<b>Clear</b>				
AIT8-009-AW-W-01C	5700-6300K	1064	52	≥ 80
AIT8-009-AW-NW-01C	4000-4500K	990	52	≥ 80
AIT8-009-AW-WW-01C	2800-3200K	937	52	≥ 80
AIT8-018-AW-W-01C	5700-6300K	2174	110	≥ 80
AIT8-018-AW-NW-01C	4000-4500K	2090	110	≥ 80
AIT8-018-AW-WW-01C	2800-3200K	1963	110	≥ 80
AIT8-022-AW-W-01C	5700-6300K	2913	130	≥ 80
AIT8-022-AW-NW-01C	4000-4500K	2684	130	≥ 80
AIT8-022-AW-WW-01C	2800-3200K	2568	130	≥ 80



22W White(Frosted)



22W Natural White(Frosted)



22W Warm White(Frosted)