

Linear Light



Accessory for surface mounting

Suspended installation

Modern, stylish, excellent surface treatment. Fully aluminum extrusion body.

Milky cover, more than 180 degree lighting angle.



LED: 2835 SMD LED chip, high luminous efficacy with reliable quality, more than 50,000 hours life time.



Size:(mm) 12W



Model number	CCT	Light output (±10%)lm	Length mm	CRI
AI-HL4040-012-AW-01W	5500-6500K	1475	606	≥80
AI-HL4040-012-AW-01NW	3900-4500K	1760	606	≥80
AI-HL4040-012-AW-01WW	2700-3200K	1385	606	≥80

Size:(mm) 24W



Model number	CCT	Light output (±10%)lm	Length mm	CRI
AI-HL4040-024-AW-01W	5500-6500K	2240	1206	≥80
AI-HL4040-024-AW-01NW	3900-4500K	2320	1206	≥80
AI-HL4040-024-AW-01WW	2700-3200K	1950	1206	≥80

Size:(mm) 36W



Model number	CCT	Light output (±10%)lm	Length mm	CRI
AI-HL4040-036-AW-01W	5500-6500K	3230	1506	≥80
AI-HL4040-036-AW-01NW	3900-4500K	3190	1506	≥80
AI-HL4040-036-AW-01WW	2700-3200K	2825	1506	≥80