


Linear Light

Accessory for recessed installation



Milky cover, more than 110 degree lighting angle.

Modern, stylish, excellent surface treatment. Fully aluminum extrusion body.

Recessed installation



LED: 2835 SMD LED chip, high luminous efficacy with reliable quality, more than 50,000 hours life time.





Model number	CCT	Light output ($\pm 10\%$)lm	Length mm	CRI
AI-RL4932-012-AW-01W	5500-6500K	1375	600	≥80
AI-RL4932-012-AW-01NW	3900-4500K	1410	600	≥80
AI-RL4932-012-AW-01WW	2700-3200K	1195	600	≥80



Model number	CCT	Light output ($\pm 10\%$)lm	Length mm	CRI
AI-RL4932-024-AW-01W	5500-6500K	1745	1200	≥80
AI-RL4932-024-AW-01NW	3900-4500K	1730	1200	≥80
AI-RL4932-024-AW-01WW	2700-3200K	1570	1200	≥80



Model number	CCT	Light output ($\pm 10\%$)lm	Length mm	CRI
AI-RL4932-036-AW-01W	5500-6500K	2290	1500	≥80
AI-RL4932-036-AW-01NW	3900-4500K	2790	1500	≥80
AI-RL4932-036-AW-01WW	2700-3200K	2490	1500	≥80