

New Model T8 Tube Light



High light efficiency, light output of frosted cover
 105-110LM/W, beam angle >160°,
 luminous area >300°,
 no shadow or dark area;
 and the lighting effect equal to
 that of traditional fluorescent tube.

Drivers are installed at two ends,
 easy to assemble, manual operation
 reduced, ensure products quality.


High brightness 2835LED,
 CRI >80, aluminum plate
 cooling to ensure long
 lifetime of LEDs.

Non-isolated driver with high
 transfer efficiency, PF value >0.9,
 suitable for 100-277 VAC,
 high anti-surge capacity.

- CE,ROHS,ERP compliant, UL pending.
- 5 years warranty, if the light operate 3 hours everyday, lifetime can up to 22.8 years.
- Suitable for indoor decoration, corridor, courtyard, warehouse, entertainment venues and other palces.




Size:(mm) 9W




A: 0.6M=603mm/23.7" L2M=1213mm/47.7"
 B: 0.6M=588mm/23.2" L2M=1198mm/47.2"
 C: 12.7mm/0.5"
 D: #27.0mm/1.06"
 E: 25.0mm/0.98"

Model number	CCT	Light output (±10%)lm	LED Q'ty	CRI
Frost				
AIT8-009-AW-W-01F	5700-6300K	945	48	≥ 80
AIT8-009-AW-NW-01F	4000-4500K	947	48	≥ 80
AIT8-009-AW-WW-01F	2800-3200K	807	48	≥ 80




AIT8-009-AW-W-01F




AIT8-009-AW-WW-01F

Size:(mm) 18W




A: 0.6M=603mm/23.7" L2M=1213mm/47.7"
 B: 0.6M=588mm/23.2" L2M=1198mm/47.2"
 C: 12.7mm/0.5"
 D: #27.0mm/1.06"
 E: 25.0mm/0.98"

Model number	CCT	Light output (±10%)lm	LED Q'ty	CRI
Frost				
AIT8-018-AW-W-01F	5700-6300K	2052	95	≥ 80
AIT8-018-AW-NW-01F	4000-4500K	2016	95	≥ 80
AIT8-018-AW-WW-01F	2800-3200K	1734	95	≥ 80



AIT8-018-AW-W-01F



AIT8-018-AW-WW-01F