


## RF Touchable Controller



Size: (mm)



LC-000W-D4-01

**Features:**

Used for Monochrome LED strip/luminaires, built-in touch button and touch ring to adjust brightness.


**Technical Parameters**

Model number	AI-000W-D4-01
Voltage	DC 12V / 24V
Output current (MAX)	8A*1CH
Output type	Common anode
Weight	105g

## RF Touchable Controller



Size: ( mm )



### LC-0RGB-D5-07

#### Features:

Compatible with any common 12V or 24V DC RGB LED strips or RGB lamps. The infrared remote control can be used to easily access 16 predefined colors as well as dimming and 22 pattern modes with pulsating, blinking, cross-fading and instant changes.

The infrared remote control has a range of up to 5 meters.


The PWM dimmer and the High-power MOS driver grant a fading without flashes up to current of 3A per channel.

#### Technical parameters

Model number	AI-0RGB-D5-07
Voltage	DC12/24V
Output current(MAX)	3A*3CH
Output power(MAX)	108W(12V input)/216W(24V input).
Channels	RGB 3 channels
Weight	22g
Control distance	>5m



Size: ( mm )



### LC-0RGB-D4-01

#### Function Descriptions:

1. 86 color modes;
2. Adjust color under the static mode;
3. Jump, fade in and out(with pause function);
4. Switch with three function modes: The first one control 5 channels Output (R,G,B,W,WW) for four or five colors LED products. The second one can control 3 channels output(R,G,B), for three colors LED product, and the third one can control 2 channels output(W,WW), for single color LED product or that with two colors. (note: four color LED product would be RGB+W or RGB+WW, five colors LED product would be RGB+W+WW, and three colors LED products would be RGB).

#### Features:


1. 5channels(R, G, B, W, WW);
2. 12/24V DC;
3. 86color patterns;
4. 20 levels for brightness adjustment;
5. Memory function;
6. Smooth dimming without flash.

#### Technical Parameters

Model number	AI-0RGB-D4-01
Voltage	12V DC/24V DC
Output current(MAX)	4A*5CH
Output power(MAX)	240W(12V input)/480W(24V input).
Channels	RGB/W/WW 5 channels
Control distance	>30m
Weight	116g
Accessories	Controller, 8 key remote pad, User manual



Size: ( mm )



### LC-0RGB-D5-06

#### Features:

Compatible with all common RGB strips and low voltage RGB lamps, Built-in 16 modes and can be controlled by a small key board. Automatically adapt to LED light which works at DC12V or DC24V. Hardware PWM dimmer without any flashes. High-power MOS driver, the whole current of the RGB three channels reaches 9A.

#### Technical parameters

Model number	AI-0RGB-D5-06
Voltage	DC12/24V
Output current(MAX)	3A*3CH
Output power(MAX)	108W(12V input)/216W(24V input).
Channels	RGB 3 channels
Weight	22g
Control distance	>30m