

Square Panel Light with Spring Installation



white housing,RAL9003.
6063 aluminum frame.
super slim 11mm thickness.

with spring installation

Use reflective sheeting
and aluminum back
cover to prevent light leaking.

3 mm thickness light guide plate,
brand: Mitsubishi from Japan.
PMMA diffuser panel with high light
transmittance.




3014 SMD LED chip, high luminous efficacy with reliable quality,
more than 50,000 hours life time.




LED driver : isolated constant current design,
Low heat, and high efficiency up to 85%,PF>0.95.




Size:(mm) 28W



Model number	CCT	Light output ($\pm 10\%$)lm	CRI
AI-PSC24CE3060-A	5500-6500K	1830	>80
AI-PSC24NE3060-A	4000-4500K	1730	>80
AI-PSC24WE3060-A	2700-3200K	1560	>80




AI-PSC24CE3060-A




AI-PSC24NE3060-A


Size:(mm) 36W



Model number	CCT	Light output ($\pm 10\%$)lm	CRI
AI-PSC24CE3012-A	5500-6500K	2610	>80
AI-PSC24NE3012-A	4000-4500K	2580	>80
AI-PSC24WE3012-A	2700-3200K	2360	>80



AI-PSC24CE3012-A



AI-PSC24NE3012-A