

Super Brightness T8 Tube Light

High light efficiency, transparent cover 140LM/W, frosted cover 120LM/W; frosted cover on the market 100LM/W, equivalent to that of CT8; no shadow or dark space.

Unique thermal management , patent design ;

UL/TUV/ERP/DLC compliant,
CRI > 80
CRI > 90 available
(light efficiency up to 120LM/W,
transparent cover),
choose 2835 high bright LED.


Rotatable and non-rotatable are available.



4 colours ■ ■ ■ ■
of end caps for optional ,aluminum +PC,
novel and unique, security and reliable.




Size:(mm)




A: 0.6M=603mm/23.7" 1.2M=1213mm/47.7" 1.5M=1513mm/59.5"
B: 0.6M=598mm/23.2" 1.2M=1198mm/47.2" 1.5M=1498mm/59.0"
C: 12.7mm/0.5"


Model number	CCT	Light output (±10%)lm	Length mm	CRI
Clear				
AI T8-009-AW-WW-01C	2800-3200K	1161	60	≥80
AI T8-009-AW-NW-01C	4000-4500K	1169	60	≥80
AI T8-009-AW-W-01C	5700-6300K	1163	60	≥80
AI T8-018-AW-WW-01C	2800-3200K	2598	120	≥80
AI T8-018-AW-NW-01C	4000-4500K	2652	120	≥80
AI T8-018-AW-W-01C	5700-6300K	2594	120	≥80
AI T8-022-AW-WW-01C	2800-3200K	3145	150	≥80
AI T8-022-AW-NW-01C	4000-4500K	3167	150	≥80
AI T8-022-AW-W-01C	5700-6300K	3215	150	≥80
AI T8-030-AW-WW-01C	2800-3200K	3990	150	≥80
AI T8-030-AW-NW-01C	4000-4500K	4050	150	≥80
AI T8-030-AW-W-01C	5700-6300K	4100	150	≥80
Frosted				
AI T8-009-AW-WW-01F	2800-3200K	1023	60	≥80
AI T8-009-AW-NW-01F	4000-4500K	1047	60	≥80
AI T8-009-AW-W-01F	5700-6300K	1037	60	≥80
AI T8-018-AW-WW-01F	2800-3200K	2180	120	≥80
AI T8-018-AW-NW-01F	4000-4500K	2276	120	≥80
AI T8-018-AW-W-01F	5700-6300K	2169	120	≥80
AI T8-022-AW-WW-01F	2800-3200K	2736	150	≥80
AI T8-022-AW-NW-01F	4000-4500K	2768	150	≥80
AI T8-022-AW-W-01F	5700-6300K	2751	150	≥80
AI T8-030-AW-WW-01F	2800-3200K	3600	150	≥80
AI T8-030-AW-NW-01F	4000-4500K	3700	150	≥80
AI T8-030-AW-W-01F	5700-6300K	3800	150	≥80



9W White(Frosted)



9W Natural White(Frosted)



9W Warm White(Frosted)