

T8 Tube Light

CRI > 80, CE and RoHS compliant, PF > 0.95,
100% 4000V high-voltage test, no glare,
no interference, human body induction.

Long lifetime, energy-saving, high bright,
high bright SMD4014 LEDs,
single-end isolated driver, good thermal
management, high lumen,
light efficiency > 110 lm/w, 5 years warranty,
highly cost-effective.




Size:(mm)




A: 0.6M=603mm/23.7' 1.2M=1213mm/47.7' 1.5M=1513mm/59.5'
B: 0.6M=588mm/23.2" 1.2M=1198mm/47.2" 1.5M=1498mm/59.0"
C: 12.7mm/0.5"


Model number	CCT	Light output ($\approx 10^3$ lm)	LED Q'ty	CRI
Clear				
AI18-009-AW-WW-02C	2800-3200K	820	52	≈ 70
AI18-009-AW-NW-02C	4000-4500K	1150	52	≈ 70
AI18-009-AW-W-02C	5700-6300K	1100	52	≈ 70
AI18-018-AW-WW-02C	2800-3200K	1680	110	≈ 70
AI18-018-AW-NW-02C	4000-4500K	2020	110	≈ 70
AI18-018-AW-W-02C	5700-6300K	2210	110	≈ 70
AI18-018-AW-WW-03C	2800-3200K	1840	130	≈ 70
AI18-018-AW-NW-03C	4000-4500K	2220	130	≈ 70
AI18-018-AW-W-03C	5700-6300K	2160	130	≈ 70
Frost				
AI18-009-AW-WW-02F	2800-3200K	630	52	≈ 70
AI18-009-AW-NW-02F	4000-4500K	770	52	≈ 70
AI18-009-AW-W-02F	5700-6300K	630	52	≈ 70
AI18-018-AW-WW-02F	2800-3200K	1480	110	≈ 70
AI18-018-AW-NW-02F	4000-4500K	1790	110	≈ 70
AI18-018-AW-W-02F	5700-6300K	1960	110	≈ 70
AI18-018-AW-WW-03F	2800-3200K	1630	130	≈ 70
AI18-018-AW-NW-03F	4000-4500K	2020	130	≈ 70
AI18-018-AW-W-03F	5700-6300K	1940	130	≈ 70



22W Warm White(frosted)



22W Natural White(frosted)



22W White(frosted)